

## FLSER COMMISSIONING TOOL

### Description

FLSER is a battery operated wireless tool using 868.30 MHz frequency for commissioning wireless transmitters, IO modules and repeaters.

After the FLTA base station has been set to work by using its own built-in buttons and display, you may set the network addresses to the wireless transmitters, IO modules and repeaters by using this FLSER tool. Each address must be unique and contains MID = 1...63 (Master ID) and SID = 1...99 (Sensor ID) or RID = 1...8 (Repeater ID).

Note! Only one unique address for each device working with one identified FLTA base station.

The FLSER tool can also be used to emulate the FLREP repeater. This feature is to ease up the installation of actual FLREP repeater and to find a suitable location for it.



#### Technical data:

Supply	3V6 AA Lithium Battery 2Ah
Transmission Frequency	868.30 MHz
Transmission Range	500m line in sight 20 ... 100m in buildings
Transmission power	+8 dBm
Reception sensitivity	-109 dBm
Modulation	Frequency Shift Keying
Ambient temperature	0... 50 °C
Ambient humidity (non condensing)	0...100 % RH
Housing	ABS-plastics, IP20

#### Ordering guide:

Model	Product number	Description
FLSER	500 501	FLSER Configurator

ClimaCheck Sweden AB, Box 46, SE-131 06 Nacka, Sweden

Tel.: +46 (0)8-50 255 250, E-post: [info@climacheck.com](mailto:info@climacheck.com)

Web: [www.climacheck.com](http://www.climacheck.com)