

FLREP-U REPEATER

Description

FLREP-U is a bi-directional repeater working on the frequency of 868.30 MHz. It is possible to use up to 8 repeaters for one FLTA base station to extend and boost the ranges of wireless transmitters in difficult environments. Each FLREP-U repeater is configured at the commissioning stage with its own repeater identification number (RID) and the base station identification number (MID). The addressing is done wirelessly by using the FLSER configuration tool. Repeaters can also be connected in series. This allows extending the distance significantly between the transmitters and the FLTA base stations. Repeaters are also aware of the transmission range of each others, so therefore the repeaters can route the signals of transmitters shortest way to the base station. Repeater is operating by listening the communication from its own base station. If the transmitter does not get the confirmation from the base station, repeater confirms the message to the transmitter instead of the base station and takes the responsibility of the message and its forwarding to the base station. FLREP-U repeaters are powered locally by a 12-30Vac/dc supply.



Technical data:

Supply	12...30V ac/dc < 0,1VA	
Frequency	868.30 MHz, Class 1	
Range	500m line in sight 20 ... 100m in buildings	
Transmission power	+8 dBm	
Reception sensitivity	-109 dBm	
Modulation	FSK	
Ambient temperature	-40 ...50°C	
Ambient humidity (non-condensing)	0...100 % RH	
Housing	IP54	
Dimensions w x h x d	115 x 180 x 45 mm	
Model	Produkt number	Description
FLREPU	500 508	Repeater outdoor

ClimaCheck Sweden AB, Box 46, SE-131 06 Nacka, Sweden

Tel.: +46 (0)8-50 255 250, E-post: info@climacheck.com

Web: www.climacheck.com